



HALL 3.1

| | |
|---|--|
| Hall floor | Asphalt with supply channels maximum load 15 (kN/sqm) |
| Suspensions from the hall ceiling | Yes Suspension points with 5 kN load per point (for vertical load only). Please note that suspension points are not available at each position and that high costs may arise in some cases. Therefore, please request a suspension points-calculation for your individual stand space in time. |
| Building height (stand size up to 30 sqm) Western bordering area Southern bordering area | min. 3.50 m – 4.00 m |
| Building height (stand size over 30 sqm) Western bordering area Southern bordering area Eastern bordering area | min. 3.50 m – 5.40 m min. 3.50 m – 5.00 m min. 3.50 m – 6.00 m |
| Illumination | The general hall lighting is reduced. Therefore, it is necessary for the exhibitors to install an own lighting system at their booth. |
| Daylight | Yes |
| Stand design | The placement in Hall 3.1 Interior Design requires a high-quality stand construction. |
| Stand construction | The minimum stand height in hall 3.1 is 3.50 m. Stands should be as open and transparent as possible on all aisle sides (at least 70%). The basic construction height is 3.50 m. Above this height, it is necessary to ensure that the rear sides of walls facing neighbouring stands are smooth and generally of a neutral colour (e. g. white or light grey). |
| Stand partition walls | 3.50 m high stand partition walls can be ordered in the Exhibitor Services Shop for EUR 25.00/rm. Please note that those partitions walls are free-standing up to 5 m. For lengths of more than 5 m, your stand must be equipped with 100 cm deep supporting walls placed at a 90 degree angle. |