



HALL CMF (Congress Center Messe Frankfurt)

| | |
|--|--|
| Hall floor | Parquet |
| Suspensions from the hall ceiling | Yes – after consultation with hall technician |
| Building height (stand size up to 30 sqm) | 4.00 m, no ceilings allowed |
| Building height (stand size over 30 sqm) | 4.50 m after consultation |
| Illumination | 580 Lux |
| Daylight | None |
| Air Conditioning | Yes |
| Fire alarm system | Smoke alarm/sprinkler |

Lifts

| Lifts No. | load-bearing capacity (kg) | loading area cabin w x l (m) | door dimensions w x h (m) |
|-----------|----------------------------|------------------------------|---------------------------|
| CMF A1 L | 5000 | 3.00 x 5.95 | 3.00 x 3.50 |
| CMF A2 P | 3000 | 1.73 x 2.30 | 1.60 x 2.10 |
| CMF A3 P | 1250 | 1.73 x 1.30 | 1.10 x 2.10 |
| CMF A4 P | 1250 | 1.73 x 1.30 | 1.10 x 2.10 |



Stand design

The stand construction should guarantee a professional presentation of all stands in the hall.

Stand construction

Stands should be as open and transparent as possible on all aisles sides (at least 70%). The basic construction height is 2.50 m. Above this height, it is necessary to ensure that the rear sides of walls facing neighbouring stands are smooth and generally of a neutral colour (e.g. white or light grey).